

A Qbic player with Smartsign.



Big difference in a small box.



Save time and avoid trouble.

Focus more on your content and less on installation and technical hassle. The Qbic player always comes with the latest version of Smartsign preinstalled. All you need to do is choose if you want a local installation or use our cloud service.

All screens, new and old.

Older screens who lack compatibility with the current signage solutions on the market can now easily be revived with a Qbic player.

A box with the little extra.

The Qbic player also supports remote access support through Teamviewer and also for maintenance purposes for IT departments. The player also supports touch screens and has built-in memory protection if something goes wrong. All in a rugged shell that can handle tough environments.



Book a personal demo

Send us an email and your number to info@smartsign.se and we will contact you. We'll review step by step how to use our smart solutions for your specific needs. When you book a demo, we will contact you and match your needs and then book an online demo. We often do this on the same day over the internet.

**Player FHD-100
from Qbic Technology**

**Product number:
SDM-QBIC-FHD100-S**



+46 10 410 77 00 / info@smartsign.se / smartsignmanager.com

Smartsign was founded in Sweden in 1998 and is now one of the world's leading digital signage software for publishing and managing internal and external communications. Today Smartsign has offices in parts of Europe, the Middle East and Australia. Smartsign's software is on displays in over 30 countries and has become the most sought after digital signage software across the industry.

The little box with the big content.



Technical specifications

Features

Operating System.....	Android 5.1
Resolution	1080p
CPU	ARM Quad-core 1.6GHz
Memory	2GB DDR3
Storage.....	8GB eMMC
Video format	H.264/MPEG- 4
Image format	JPEG/PNG
Orientation display	Landscape and portrait
Audio format.....	MP3

IO-interface

Ethernet	1 x RJ45 (10M/100M)
WLAN	802.11 b/g/n, with 2dB antenna
HDMI	1 x HDMI 1.4a with CEC
USB	3 x USB2.0 / 1 x Micro USB (ADB)
Analog stereo out	1 x 3.5mm stereo
Digital stereo out	1 x SPDIF
COM	1 x RS-232 port
Expansion storage.....	1 x Micro SDHC slot

Mechanical and environment

Dimension (WxDxH).....	139x128x30 mm (S.47"x5.04"x1.18")
Weight	510g (1.21 lbs)
Mounting	Easy wall mount
Housing	Aluminium
Operating Temperature	0~50°C
Storage Temperature.....	-20°C to 60°C
Humidity	5% to 90% (non-condensing)
Power	DC 12V, 1.5A
Certification	CE/FCC/RoHS
Warranty	1 year

FHD-100

